Application No.: 10/581,075

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the

application:

LISTING OF CLAIMS:

1. (currently amended): A gas sensor comprising:

a gas detection element;

a ceramic wiring substrate on which the gas detection element is mounted; and

a protective cap which is attached to the ceramic wiring substrate in such a manner as to

cover the gas detection element, the protective cap-and-which is made of metal- and defines,

when attached to the ceramic wiring substrate, a gas-measuring space in cooperation with the

ceramic wiring substrate, and has a gas intake for introducing gas to be measured into the gas-

measuring space from the outside thereof;

wherein the gas detection element is mounted in a cavity of the ceramic wiring substrate;

wherein the gas detection element includes a diaphragm structure section which is formed

of a silicon substrate, and the diaphragm structure section includes a gas detection portion;

wherein the ceramic wiring substrate has a multilayer structure in which a plurality of

ceramic dielectric layers are laminated; a recess is formed on a portion of a side surface of the

ceramic wiring substrate which corresponds to a side surface of a ceramic dielectric layer other

than an uppermost ceramic dielectric layer which forms a top surface of the ceramic wiring

substrate;

wherein the protective cap is held on the ceramic wiring substrate in a nonadhering

condition; and

2

Application No.: 10/581,075

wherein the protective cap has a perpendicularly projecting portion extending along the side surface of the ceramic wiring substrate; and an engagement projection to be fitted into the recess is formed on the perpendicularly projecting portion.

- 2. (canceled).
- (canceled).
- 4. (currently amended): A gas sensor according to <u>claim 1 elaim 3</u>, wherein the ceramic wiring substrate has a substantially quadrangular shape as viewed along the direction of lamination of the multilayer structure and the recess is formed on each of at least two opposed side surfaces of the ceramic wiring substrate.
- 5. (currently amended): A gas sensor according to <u>claim 1elaim 3</u>, a guide recess is formed on the side surfaces of the ceramic wiring substrate so as to guide the perpendicularly projecting portions to locations where the engagement projections are fitted into the corresponding recesses.
- (previously presented): A gas sensor according to claim 1, wherein the gas
  detection element includes a diaphragm structure section, and the diaphragm structure section
  includes a gas detection portion;

the protective cap has a plurality of the gas intakes formed in a ceiling portion in opposition to a mounting surface of the ceramic wiring substrate on which the gas detection element is mounted; and

the plurality of gas intakes are formed such that when the gas intakes are viewed from the outside of the ceiling portion along a direction perpendicular to the mounting surface, the diaphraem structure section of the gas detection element is invisible therethrough.

3

Application No.: 10/581,075

7. (original): A gas sensor according to claim 6, wherein element-side

electrodes are provided on the gas detection element;

substrate-side electrodes are provided on the ceramic wiring substrate;

connection portions are provided for connecting the

element-side electrodes and the corresponding substrate side electrodes; and

the plurality of gas intakes are formed such that when the gas intakes are viewed from the

outside of the ceiling portion along a direction perpendicular to the mounting surface, the

connection portions are invisible therethrough.

8. (currently amended): A gas sensor according to claim 1, wherein the gas detection

element includes the diaphragm structure section, and the diaphragm structure section includes

the gas detection portion;

athe ceramic wiring substrate has a multilayer structure in which a plurality of ceramic

dielectric layers are formed such that inner wiring layers are sandwiched therebetween;

and

a recess is formed on athe ceramic dielectric layer among the plurality of ceramic

dielectric layers on which the gas detection element is mounted, in a region in opposition

to the diaphragm structure section.

9. (previously presented): A gas sensor according to claim 1, wherein a bottom

surface of the ceramic wiring substrate which is located opposite a side where the gas detection

element is mounted is formed substantially planar, and outer electrodes to be electrically

connected to a circuit board to which the gas sensor is fixedly attached are formed on the bottom

surface.

4

Application No.: 10/581,075

10. (currently amended): A gas sensor according to claim 1, wherein a plurality of the gas detection elements which respond to different gas species are mounted on the ceramic wiring substrate.